



ACCU-TEXTURE
T70256000F

Product Description

Texturi Accu-Texture is a 100% acrylic interior coating applied in two applications; as the base coat and finish texture. Texturi Accu-Texture offers durability, mold and mildew resistance and integral color in a decorative interior texture finish. It is commonly applied as an orange peel, splatter or knockdown finish. Texturi Accu-Texture is recommended for use on interior walls and ceilings in hospitality and multi-family environments.

Features

- 100% Acrylic
- Extremely Durable, Resists Abuse
- Integral color
- 5 year Limited warranty against surface mold and mildew growth
- Smooth Non-Gritty Feel

Certification

- Not manufactured with lead, mercury or chromate containing materials
- Not manufactured with crystalline silica or ethylene glycol
- Meets LEED and SCAMD product requirements for air quality

Technical Specifications

Solids

By Volume- 44% ± 2%

Vehicle Type

100% Acrylic

VOC

40 g/l, .33 lbs/gal

Volume per pail

600 fl oz or 4.688 gallons

Finish

Flat, Sheen <2% @ 60

Drying Time

- Dries to the touch in 1 hour, may be recoated after 4 hours depending on temp and humidity

Coverage

500-600 sq ft / pail

Coverage may vary due to application technique, ambient temperature, surface temperature, surface porosity, and/or application methods.

Application

Texturi Accu-Texture Finish must be mixed thoroughly prior to use. Inter-mix pails to ensure color consistency. Texturi Accu-Texture must achieve 90% coverage of the basecoat application with the texture applied to achieve maximum durability. A variety of common orange peel, splatter and knockdown textures can be achieved with common texture spray equipment and appropriate hand tools (for knockdown effect), including texture pumps, hoppers and some pneumatic machines. Application method will depend on selected finish.

Drying

DO NOT apply product when the ambient surface temperature is below 40°F (4°C) or above 90°F (32°C). Protect all work from inclement weather with an approved system until cured.

Drying time may vary due to climatic conditions. Ambient air and surface temperature must be above 40°F (4°C) during application and dry time.

Surface Preparation

Substrates are clean and free of loose material, dirt and dust, efflorescence, grease, oils, curing agents, and cleaning solutions. All surfaces must be smooth and free of irregularities. Repair all cracks with the appropriate patching material for the existing substrate. Painted or glossy surfaces must be dulled to promote adhesion.

Thinning & Clean-up

A small amount of water, not more than 16 ounces, may be added to each pail. If water is added, the same amount must be added to each pail to ensure color consistency.

Clean with soapy water before drying.

Cautions

WARNING! DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN

-Protect from freezing

WARNING! If you scrape, sand or remove old paint you may release lead dust. LEAD IS TOXIC, EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMAN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect you and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

Warranties

Comex warrants that its products will conform and perform in accordance with the product specification sheet. Comex also warrants its products to be free from defects in material and manufacturing.



5575 DTC Parkway
Suite 100
Greenwood Village, CO 80111

Made in the U.S.A.

www.thecomexgroup.com

These suggestions and data are based on information we believe to be reliable. They are offered in good faith and limited guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them. Specifications are subject to change without notice.

OCOTBER 2010