

Product Description

Texturi Acrylic Surfacer can be used as a primer or surfacer over drywall; as the basecoat of a two step interior wall texture system. This system creates an extremely durable, mildew resistant finish and is applied with an orange peel, splatter or knockdown finish (Texturi Acrylic Texture Finish). The material is applied over level 3 drywall finish, with airless spray equipment. It is tinted to the same color as the Texturi Finish. When applied in this manner, a perm rating of 66 is achieved. Texturi Acrylic Surfacer can be used as a finish over the Texturi Interior Wall System when repainting larger areas is required. This application maintains the permeability rating of the system, as well as the original warranty. It is also used in the Texturi Anti-Abuse System when applied 30-35 mils dry in three coats. Texturi Acrylic Surfacer can be used as an exterior primer over cured cement, concrete, stucco, masonry, and tilt-up walls, before applying a Texturi Acrylic Finish.

Features

- Acrylic Based
- Interior and Exterior Use
- Great Adhesion
- Extremely Durable and Hard
- Highly Permeable
- Easy water & soap clean-up

Certification

- Not manufactured with lead, mercury or chromate containing materials
- Meets LEED and SCAMD product requirements for air quality
- Water vapor transmission (ASTM D1653 method B): 66 perms
- Abrasion (ASTM D4060-C5-17 wheel 1 Kg tabor 1,000 cycles): Passed
- Salt spray resistance (ASTM B117): Passed
- Accelerated weathering (ASTM G154): Passed
- Mildew resistance (ASTM D3273): Passed
- Flame spread (ASTM E840): FSI <20, Class A
- Abrasion resistance (ASTM D969): Passed

Technical Specifications

Solids
By Volume- 57 ± 2%

Vehicle Type
Acrylic

VOC
<50 g/l

Volume per pail
5 gallons

Drying Time
- Dries to touch: 2-4 hours

Coverage
650 sq. ft. / pail at 10.5 mils wet, 6mils dry for Interior Wall System.
115-130 sq.ft./ pail at 30 mils dry for the Anti-Abuse System.
800-1000 sq. ft./ pail at 4 mil dry as an exterior primer.

Application

Apply a uniform coat of Texturi Acrylic Surfacer at 10.5 mils wet as part of the Interior Wall System when used as a base. Apply three uniform coats of Texturi Acrylic Surfacer at 18 mils wet as part of the Anti-Abuse System. Apply a uniform coat of Texturi Acrylic Surfacer at 7 mils wet as an exterior primer. Use of a 1.0 gpm airless pump, with a .021-.023 tip is recommended to the substrate. Remove gun filter before spraying.

Drying
DO NOT apply product when the ambient surface temperature is below 40°F (4°C) or above 90°F (32°C). Protect all work from inclement weather with an approved system until cured. Drying time may vary due to climatic conditions. Ambient air and surface temperature must be above 40°F (4°C) during application and dry time.

Curing
One coat stucco and masonry products must cure for a minimum of 7 days and concrete must be cured for a minimum of 28 days. The pH level of these products must be below 10 prior to application of Texturi Acrylic Surfacer as primer.

Surface Preparation
Substrates are clean and free of loose material, dirt and dust, efflorescence, grease, oils, curing agents, and cleaning solutions. All surfaces must be smooth and free of irregularities. Repair all cracks with the appropriate patching

material for the existing substrate. Painted or glossy surfaces must be dulled to promote adhesion.

Thinning & Clean-up

Thinning is not required, or recommended. Clean with soapy water before drying.

Cautions

WARNING! DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN

-Protect from freezing

Warning! If you scrape, sand or remove old paint you may release lead dust. LEAD IS TOXIC, EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMAN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect you and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

Warranties

Comex warrants that its products will conform and perform in accordance with the product specification sheet. Comex also warrants its products to be free from defects in material and manufacturing.

5575 DTC Parkway
Suite 100
Greenwood, CO 80111

Made in the U.S.A.

www.thecomexgroup.com

These suggestions and data are based on information we believe to be reliable. They are offered in good faith and limited guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them. Specifications are subject to change without notice.

OCTOBER 2010