



CREMA BASE COAT T70256360F

Product Description

Texturi Crema Base Coat is a water-based, high solid, elastomeric sealant. This product provides exceptional flexibility over joints in drywall, cement board, composite siding, magnesium board and a variety of other siding products. The thick, creamy consistency allows for easy application on vertical substrates.

Features

- Excellent durability and flexibility
- Elastomeric based
- For drywall, masonry, stucco, concrete, composite siding, MgO board and a variety of other siding materials
- Smooth application, easy to apply product.
- Manufactured with special fungicides to protect coatings film.
- Low volume loss.
- Easy water and soap clean up

Certification

- Not manufactured with lead, mercury or chromate containing materials
- Meets LEED and SCAMD product requirements for air quality

Technical Specifications

Solids

By Volume- 69% ± 2%

Vehicle Type

Elastomeric

VOC

<50 g/l

Weight per gallon

7.5 lbs

Drying Time

To touch - Dries within 24 hours

Coverage

Varies by application

Application

Texturi Crema Base Coat applies easily with a stainless steel trowel or 6" mud knife. Apply material to joints, embedding 2 oz. or 4.5 oz mesh, trowel smooth to depth of mesh.

Drying

DO NOT apply product when the ambient surface temperature is below 40°F (4°C) or above 90°F (32°C). Protect all work from inclement weather with an approved system until cured.

Drying time may vary due to climatic conditions. Ambient air and surface temperature must be above 40°F (4°C) during application and dry time.

Primers

No primer is recommended. Cement Band masonry products must cure for a minimum of 7 days and concrete must be cured for a minimum of 28 days. The pH level of these products must be below 10 prior to application of the basecoat.

Surface Preparation

All surfaces must be clean, dry, firm and free of dirt, grease, oil, wax, efflorescence and other contaminants.

Thinning & Clean-up

Product should not be reduced. Clean with clean soapy water immediately after use.

Cautions

WARNING! DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN

-Protect from freezing

WARNING! If you scrape, sand or remove old paint you may release lead dust. LEAD IS TOXIC, EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMAN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect you and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

Warranties

Comex warrants that its products will conform and perform in accordance with the product specification sheet. Comex also warrants its products to be free from defects in material and manufacturing.



5575 DTC Parkway
Suite 100
Greenwood Village, CO 80111

Made in the U.S.A.

www.thecomexgroup.com

These suggestions and data are based on information we believe to be reliable. They are offered in good faith and limited guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them. Specifications are subject to change without notice.

OCTOBER 2010